

# COMPACT THERMOSTAT



- Simple to Mount
- High Switching Performance
- Large Setting Range
- Small Size

## TECHNICAL PARAMETER

Product Code **IED-KTO | IED-KTS**

Contact Type Normally Closed | Open

Setting Range 0 to 60 °C

Switch Difference 7% K (±4% tolerance)

Contact Resistance < 10m Ohm

Max. Switching capacity 250 VAC, 10(2) A / 120VAC,  
15(2) A

DC 30W At 24VDC To 72VDC

Connection 2-pole terminal for 2.5mm<sup>2</sup>,

Rigid wire : 2.5mm<sup>2</sup>

Stranded wire : 1.5mm<sup>2</sup>

Mounting 35mm DIN rail, EN50022

Casing Plastic Acc. to UL94 V-0

Operating Temp. -20 To +80°C

Weight 60 gm

Certification CE, RoHS Compliance

## CLIMATE CONTROL



25°C



## AUTOMATION SYSTEMS & SOLUTION

Address: T-12, 3<sup>rd</sup> Floor, Pankaj Central Market, I.P. Extension, Patparganj, Delhi – 110092

Tel: +91 11 41709077 / 22232187

Email: [infoautomation18@gmail.com](mailto:infoautomation18@gmail.com)

[www.automationsystem.in](http://www.automationsystem.in)